

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
ANYA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PROGRATION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O.C.C.

MISCELLANEOUS NOTICES

NOV 20 10 38 AM '63

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

11-19-63
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the
Cities Service Oil Company

Well No. 1 in (Unit)

NE NW 16 11S 38E Echols Dev. East
(40-acre Subdivision) 1/4 of Sec. T. R. NMPM. Pool
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to a TD 12089' 13 3/8" set @ 383.54' w/375 sxs. 8 5/8" set @ 4414.20 w/1535 sxs. 5 1/2" set @ 12087.57 w/600 sxs. 5 1/2" csg. was perforated opposite the Devonian formation and produced until proven non-commercial.

It is proposed to P & A this well in the following manner: (1) load hole w/mud laden fluid; (2) set 25 sack cement plug on bottom; (3) set 35 sack cement plug where 5 1/2" csg. is shot off, half of plug above and half of plug below stub; (4) 35 sack cement plug @ 4554-4274; (5) if 5 1/2" csg. is recovered below 6459' 25 sacks cement plug set @ 6559-6359; (6) set 10 sack cement plug to surface w/4" marker extending 4' above ground level to designate P & A location; (7) location will be cleared of all equipment and debris, pits will be leveled and cellar filled in a workman like manner.

Approved....., 19.....
Except as follows:

Cities Service Oil Company

Company or Operator

By [Signature]
District Superintendent

Position.....
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

Name.....
G.M. Geyer
Address.....
Box 69 - Hobbs, New Mexico