

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Los Nietos Company

200 Wilkinson-Foster Building, Midland, Texas

Elliott

Well No. 1 Company or Operator in SE/4 of Sec. 27 Lease, T. 11S

R. 38E, N. M. P. M., Wildcat Field, Lea County.

Well is 4620 feet south of the North line and 660 feet west of the East line of Section 27

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is L.E. Elliott (L.C. 069051) Address Roswell, New Mexico

The Lessee is Address

Drilling commenced May 26 19 51 Drilling was completed November 30 19 51

Name of drilling contractor The Zephyr Corporation Address 1111 First Nat'l. Bank Bldg.

Elevation above sea level at top of casing 3901 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 12,140 to 12,148.5 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 9,850 to 9,900 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
11-3/4	42#	8Rd	Nat'l.	332'	None	--	--	--	Surface
8-5/8	28#-32#	8Rd.	Youngstown	4553'	Guide	1200	--	--	Salt String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	11-3/4	332	300	P&P		
11"	8-5/8	4553	10.0	P&P		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment Subject well was not shot or treated with chemicals

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 12,272 feet, and from feet to feet.

Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to producing (No production) 19

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

R.H. Webb Driller Otto Coppock Driller

John Strahan Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 10th

Midland, Texas December 10, 1951

day of December, 1951

Name

Position Drilling Superintendent

Representing Los Nietos Company Company or Operator.

Address Midland, Texas

HELEN M. NICHOLS

Notary Public

My Commission expires June 1, 1953

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
1200	2340	1140	Red Beds and Sand. Top Rustler 2340.
2340	2410	70	Anhydrite and Red Beds Top Salt 2410
2410	2895	485	Salt, Red Beds and Anhydrite Base Salt 2895
2895	3100	105	Anhydrite Top Yates 3100
3100	4450	1350	Sand, Anhydrite, Salt and Red Beds Top San Andres 4450
4450	5060	610	Dolomite and Anhydrite
5060	5260	200	Dolomite
5260	5905	645	Dolomite and Lime Top Glorieta 5905
5905	6570	575	Sand, Shale, Anhydrite and Dolomite Top Clear Fork 6570
6570	7130	570	Dolomite with some sand, anhydrite, shale and chert. Top Tubb 6130
7130	7810	680	Dolomite, sand and anhydrite Top Abo 7810
7810	9110	1300	Red, Green and Gray Shale and Dolomite Top Hueco 9110
9110	10770	1660	Lime, Chert, and Shale
10770	11050	280	Cherty Lime, Chert and Shale Top Bend 11050
11050	11422	372	Lime, Sand and Shale Top Mississippian 11422
11422	11981	559	Lime and Chert
11981	12017	36	Sand, Lime and Shale Top Woodford 12017
12017	12088	71	Brown to black Shale Top Devonian 12088
12088	12168	80	Dolomite
12168	12272	104	Dolomite and Chert.

John W. Johnson
Geologist