

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission, or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)April 18, 1955  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Jack Markham et al Pure-State

(Company or Operator)

Well No. 1 in Unit E

(Unit)

SW 1/4 NW 1/4 of Sec. 32, T-11-S, R-38-E, NMPM, Wilbont Pool  
(10-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Total depth 5155 feet in San Andres dolomite. 5½-inch casing cemented at 5080 feet with 800 sacks. Treated open hole 5080 to 5155 feet with 1000 gallons mud clean-out agent and 2500 gallons gelled acid. After recovering load, snabbed 10 barrels salt water with very slight show gas plus approximately 5% oil in total fluid per day.

We propose to plug and abandon this well as follows: (1) load hole with mud; (2) place 10 sacks cement in 5½-inch casing at 5075; (3) pull recoverable 5½-inch casing (estimate a maximum of 2000 feet); (4) place 30-sack cement plug at 700 feet; (5) place 10-sack cement plug and regulation marker in 8-5/8-inch casing at surface.

Notes: This plan approved orally by Mr. S. J. Stanley.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Jack Markham et al

(Company or Operator)

By.....

L. O. Storm

Position.....

Engineer

Send Communications regarding well to:

Name Jack Markham

Address 1114-10th Street, Lubbock, Texas