

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0558135

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR ESTATE NAME

Davis Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Bough (Perma-Penn)

11. SEC., T., R., NE, OR SW, AND
SURFACE OR AREA

Sec. 7, T-9-S, R-36-E

12. COUNTY OR PARISH 13. STATE

Lea New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TENNECO OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 1031 - Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface660' FSL & 660' FWL, Section 7, T-9-S, R-36-E,
Lea County, New Mexico.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

4107 GR 4117 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Re-entry

(NOTE: Report results of multiple completion or Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.)*

Began re-entry operations 7-29-69 and completed, with well producing on 8-7-69 in open hole from 9626 to 9663 in Bough "C".

Re-entered 5 1/2" casing (shot-off point) at 3571'. Casing was cemented back into 8 5/8" casing (set @ 4383') with cement top approximately 3600'. The 5 1/2" casing was cleaned out to casing shoe @ 9629' and open hole from 9629 to T.D. @ 9663'. The open hole section was acidized with 1,000 gallons 15% NE acid.

(Prior to drilling cement retainer @ 9534', and cement below, the 5 1/2" casing string was pressure-tested to 2000 PSI for 30-min., o.k.) After acid was swabbed back, well was placed on hydraulic lift.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Drilling Supt.

DATE

8-19-69

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

AUG 22 1969

*See Instructions on Reverse Side

J. L. GORDON
DISTRICT ENGINEER

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local, Federal, and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; and/or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site condemned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1969-O-685229
 PO 837-499 867-851

This image shows a blank, aged, cream-colored page, likely an endpaper or flyleaf of a book. The paper has a slightly textured appearance with some minor discoloration and faint, illegible markings, possibly from the reverse side or due to age. The left edge of the page shows the binding of the book, with visible stitching and the inner cover material. The overall tone is warm and vintage.