

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other Instructions on Re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. N.M. 25413
2. NAME OF OPERATOR The Maurice L. Brown Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Suite 200/Sutton Place Bldg. Wichita, Kansas 67202		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Letter M, 660' from South line, 660' from West line of Section 8, Township 9-S, Range 36-E.		8. FARM OR LEASE NAME KCS 686 Ltd.
14. PERMIT NO.	15. ELEVATIONS (Show whether DG, RT, GR, etc.) 4100' KB, 4091.4 GR.	9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Vada Penn
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8, T-9-S, R-36-E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) Re-entry ☒FILL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Progress report ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-21-80 through 4-23-80

Recovered twisted off drill string.

4-24-80 through 4-29-80

Dressed off top of 4 1/2" casing and ran 113 joints of 4 1/2" casing with casing bowl. Latched onto 4 1/2" casing top at 3550' depth and landed casing on well head.

4-30-80 through 5-2-80

Cleaned out inside 4 1/2" casing to top of bottom plug at 9704'.

5-9-80 through 5-19-80

Pressure testing and swab testing to locate a casing leak. Cemented shot point in casing which was leaking at 6500' depth through a cement retainer set at 6431' depth and using 200 sacks of Class "H" cement. Job complete at 6:37 P.M. on 5-19-80.

RECEIVED

MAY 22 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. M. Brown

TITLE

District Engineer

DATE

5-20-80

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

FOR RECORD

MAY 27 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side