

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 25418
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

The Maurice L. Brown Co.

3. ADDRESS OF OPERATOR

Suite 200, Sutton Place Bldg., Wichita, Kansas 67202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

Unit Letter M, 660' from South line, 660' from West
line, of Section 8, Township 9-S, Range 36-E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4100' KB, 4091.4 GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

KGS 686 Ltd

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Vada Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T-9-S, R-36-E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) Reentry ☒PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drill out surface plug and clean out to top of 7" casing at 264'.
2. Dress out top of 7" casing, enter 7" casing and clean out to top of 4½" casing at 3015' and pressure test casing.
3. Dress out top of 4½" casing and clean out to top of cast iron bridge plug and pressure test.
4. Drill cast iron bridge plug at 9650' and clean out to 9730'.
5. Complete in original Bough "C" perforations from 9714' to 9728'.
6. Install pumping equipment.
7. Pump Test Well.

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICONote: This is a reentry of an old well on existing well pad.
No land will be disturbed off the original well and pit location.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. Brosbeck

TITLE District Engineer

DATE 3-5-80

(This space for Federal or State office use)

TITLE

DATE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

MAR 21 1980

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED

MAR 26 1980

OIL CONSERVATION DIV.