

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

OCT 12 1969

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. NM-380
7. Unit Agreement Name
8. Farm or Lease Name State "O"
9. Well No. 2
10. Field and Pool, or Wildcat South Crossroads Dev.
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Texas Pacific Oil Company
3. Address of Operator P.O. Box 1069 Hobbs, New Mexico
4. Location of Well UNIT LETTER <u>O</u> , <u>1980</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>15</u> TOWNSHIP <u>10</u> RANGE <u>36</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3985

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set cast iron bridge plug at 12,261'.
2. Loaded hole with mud laden fluid.
3. Cut & pulled approximately 4820' of 5½" casing.
4. Spotted 25 sack cement plug at stub of 5½" - 4820'.
5. Spotted 25 sack cement plug at bottom of 8 5/8" - 4260'.
6. Spotted 10 sack cement plug at the top of hole.
7. Installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. Schmerler TITLE Asst. Mgr. DATE 9-2-69
APPROVED BY Nathan E. Olegg TITLE OIL & GAS INSPECTOR DATE MAR 1 1972
CONDITIONS OF APPROVAL, IF ANY: