

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Sawyer Formation San Andres County Lea
Initial _____ Annual X Special _____ Date of Test 2-5-64
Company Sinclair Oil & Gas Co. Lease Federal Kelly A Well No. 2
Unit G Sec. 19 Twp. 9S Rge. 38E Purchaser Sinclair Oil & Gas Co. Plt. #29
Casing 7 5/8 Wt. 15.3 I.D. _____ Set at 400' Perf. _____ To _____
Tubing 2 7/8 Wt. 6.5# I.D. 2.441 Set at 5050 Perf. 4896 To 4938
Gas Pay: From 4896 To 4938 L 4896 xG .900 -GL 3917 Bar.Press. 13.2
Producing Thru: Casing _____ Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: _____ Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Proven) (Choke) (Meter)Type Taps Flg.

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						1306				72
1.	3	1.375	419	2	61	331				24
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	11.94	29.41	432.2	.9990	.8660	1.074	326.2
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio Neg. cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
P_c 5.866 (1-e^{-s}) .236

Specific Gravity Separator Gas .800
Specific Gravity Flowing Fluid _____
P_c 1319.2 P_c² 1740.3

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.	344.2	118.5	1.913	3.660	.8638	119.3	1621.0	345.5	26.19
2.									
3.									
4.									
5.									

Absolute Potential: 350.3 MCFPD; n Previous n Slope Used (1.000)

COMPANY Sinclair Oil & Gas Co.
ADDRESS Box 1470 Midland Texas Mr. Fred Rogers
AGENT and TITLE R. Fawcett BME Inst. Tech. Checked By W.R. Lord
WITNESSED None
COMPANY _____

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressibility factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .