

COUNTY	LEA	FIELD	Inbe	MN	20093
STATE	NM	OWWO			
OPR	PUBCO PET. CORP.			MAP	
	1 British American-State				
	Sec 23, T-10-S, R-33-E			CO-ORD	
	660' FSL, 1980' FEL of Sec.				
	Re-Cmp 11-28-69	CLASS	EL		
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
10 3/4" at 427' w/400 SX					
8 5/8" at 4018' w/450 SX					
4 1/2" at 9810' w/400 SX					
LOGS EL GR RA IND HC A					
	TD 9810'	PBD 9345'			

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	9691'	TYPE	WO
DATE				

F.R.C. 6-25-70; Opr's Elev 4212' KB
 PD 9691' - WO - Pennsylvanian
 (Orig. Boren, Sam & Major and Giebel Oil
 Co. cmp 6-24-63 thru Perfs 9771-76', OTD
 9810')

6-22-70 TD 9810', PBD 9345', TEMPORARILY ABANDONED
 Perf 9466-74', 9654-58', 9664-72', 9686-91'
 w/2 SPF
 Acid (9654-91') 500 gals
 Swbd dry (9654-91')
 Acid (9466-74') 500 gals
 Swbd dry (9466-74')
 PB to 9345'
 Perf 9162-67', 9202-07' w/2 SPF
 Acid (9162-9207') 500 gals
 Swbd dry (9162-9207')

6-25-70 COMPLETION REPORTED

COUNT	Lea	FIELD	South Lane-Penn.	STATE	N.M.	NO.	
OPR	Sam Boren & Major & Giebel Oils	MAP					
NO	1	LSE	British-American State				
SEC	23	T.	10S	BLK.	33E	SUR.	CO-ORD.
LOC	660' fr S Line & 1980' fr E Line of Sec.						
MI.	FROM	CLASS.	EL 42072				
SPUD.	4-16-63	COMP.	6-24-63	FORMATION	DATUM	FORMATION	DATUM
IRI	3500 gals acid			Core Top:			
				Bough "C"			
CSG. & SX.				9760			
10 3/4"	427'	400		LOG:			
8 5/8"	4018'	450		Bough "C"			
4 1/2"	9810'	400		9760			
TBG.	DEPTH	SIZE					
LOGS	EL	GR	RA	IND	HC	A	
				TD	9810'	ls. & sh.	PB
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
9771-76'	Flo. 221 BO + 55 BW	1 1/2"			50.		175#
(Bough "C")							24'
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	Forester Drlg. Co.	PROP DEPTH	9950'	TYPE			
DATE							

F.R. 4-18-63, Bough "C". Oper's Elev. 4211' DF
 PD 9950', Forester Drlg. Co.

4-22-63 Drlg. 3993'.
 4-29-63 Drlg. 4990' ls.
 5-6-63 Drlg. 7445' ls.
 5-13-63 Drlg. 8647'
 5-20-63 Drlg. 9271' ls.
 5-27-63 TD 9810', running casing.
 Cored 9725-47', rec 22' ls. & sh., NS.
 Cored 9747-78', rec 31' ls. & sh., w/fair poro. &
 show 9763-66' & good poro. & fair show 9772-78'.
 Cored 9778-9810', rec 32' being: 2' ls., vuggy w/
 fair show, 30' ls. & sh., NS.

6-3-63 TD 9810' ls. & sh., WOC.
 6-10-63 TD 9810' ls. & sh., prep to perf.
 6-17-63 TD 9810' ls. & sh., swbg.
 Perf 20/9771-76', treated 500 gals acid, re-treated
 1000 gals acid, re-treated 2000 gals acid.
 Swbd AW, w/tr. gas & slight show oil.
 6-24-63 TD 9810' ls. & sh., COMPLETED.