

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cabot Inc.	8. Field or Lease Name State - N (N)
3. Address of Operator Box 1101 Pampa, Texas	9. Well No. 1
4. Location of Well UNIT LETTER A 1980 FEET FROM THE N LINE AND 2350 FEET FROM THE E LINE, SECTION 35 TOWNSHIP T-10-S RANGE R-33-# NMPM.	10. Field and Pool, or Wildcat Lane
15. Elevation (Show whether DF, RT, GR, etc.) 4206	12. County Lee

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE 133/8

133/8" set at 371' with 350 sack cir.
8 5/8" set at 3964' with 300 sack
4 1/2" at 9830' with 150 sack
Perforations at 9770' 74'
This well has become non-productive of oil or gas and will be plugged and abandoned in the following manner.
CIBP with 20' cement at 9500'
Cut and pull 4 1/2" casing
25 sack cement plug across stub of 4 1/2"
25 sack cement plug at 5360' (Glorieta)
25 sack cement plug at 8 5/8 casing shoe
cut and pull 8 5/8 casing
25 sack cement plug across stub of 8 5/8"
25 sack cement plug at 13 3/8' casing shoe
10 sack cement plug at surface 4' dry hole marker
Mud laden fluid will be place between plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

DATE

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 2 1970

**OIL CONSERVATION COMM.
HOBBS, N. M.**