

COUNTY	Lea	FIELD	Lane-Pennsylvanian	STATE	N.M.	NO.	
OPR	Boren, Sam & Major & Giebel Oils	South	MAP				
NO.	1	LSE	Humble "B"				
SEC.	34	T.	10S	BLK.	33E	SUR.	CO-ORD.
LOC.	1980' fr N Line & 660' fr E Line of Sec.						
MI.		FROM		CLASS.		EL.	4209E
SPUD.	6-1-63	COMP.	8-16-63	FORMATION	DATUM	FORMATION	DATUM
IRT.	1000 gals acid			Core Top:			
				Bough "C"			
CSG. & SX.				9686			
	10 3/4"	425'	400				
	7 5/8"	3998'	450	LOG:			
	4 1/2"	9740'	400	Bough "C"			
TBG.	DEPTH	SIZE		9691			
LOGS	EL GR RA IND HC A			TD 9740'		PB 9730'	
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
9693-9701'	Ppd. 216 BO + 200 BW				44.		24'
(Bough "C")							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	Hisson Drlg. Co.	PROP DEPTH	9900'	TYPE			
DATE							

F.R. 5-31-63, Bough "C"
 PD 9900' - Hisson Drlg. Co., Contractor
 6-10-63 TD 3998', WOC.
 6-17-63 Drlg. 5271' ls.
 6-24-63 Drlg. 7285' ls. & sh.
 7-1-63 Drlg. 8402' ls.
 7-8-63 Drlg. 9126' ls.
 7-15-63 Coring @ 9679'.
 Cored 9630-78', rec 48' ls. & sh., w/good poro. &
 fair show in lime 9651-61'.
 DST 9649-78', open 1 hr, GTS 7", rec 250' oil
 (Grav. 46.5 deg.), 12' GC Salt Wtr, 15" ISIP 3362#,
 FP 35-64#, 30" FSIP 2802#.
 7-22-63 TD 9740', prep to log.
 Cored 9678-9715', rec 37' ls. & sh., w/poro. &
 stain in lime 9694-9705'.
 Cored 9715-40', rec 25' ls. & sh.

Boren, Sam & Major & Giebel Oils, #1 Humble "B" - Sec.
34-10S-33E

7-29-63 TD 9740', WOC.
8-5-63 TD 9740', RU Kobe Pump.
Perf 32 shots 9693-9701', treated 1000 gals Acid.
Swbd 100 BF (30% oil) in 11 hrs.
8-12-63 TD 9740', WO Electricity.
8-19-63 TD 9740', tstg. on Kobe Pump.
Ppd. 200 BO + 150 BW in 24 hrs.
8-26-63 TD 9740', COMPLETED.