YATES PETROLEUM CORPORATION Carper McAlester ATE State #1 Section 25-T11S-R34E Lea County, New Mexico

SUNDRY NOTICE CONTINUED:

ì

up tree on top of BOP. Loaded annulus with 83 bbls 2%. Tested packer to 1000#. Swabbed tubing dry, Shut well in. 10-26-99 - Rigged up treesaver. Acidized perforations 12197-1228' (Morrow) with 1000 gallons 7-1/2% Morrow acid with 25% methanol and 1000 scf/bbl N2 and ball sealers. Rigged down treesaver. Flowed well for cleanup. Shut well in. 10-27-99 - Flow tested. Shut well in. 10-28-99 - Bled well down. Swabbed and flow tested. Shut well in. 10-29-99 - Bled well down. Swabbed tubing dry. Loaded with 2% KCL with clay stabilizer and surfactant. Opened bypass and circulated 100 bbls. Pulled packer to 5600'. Swabbed tubing and annulus dry to 5000'. TOOH. Secured well. 10-30-11-1-99 - Prep to frac. 11-2-99 - Rigged up casing saver. Frac'd perforations 12197-1228' (Morrow - via 4-1/2" casing) with 57000 gallons 700 binary and 70000# 20-40 interprop. Shut well in for 2 hours. Rigged down treesaver. Flowing well for cleanup. 11-3-99 - Flow tested. Shut well in. 11-4-99 - Flow tested. Rigged up wireline. TIH with 3.795" OD gauge ring and junk basket to 12200'. TOOH with wireline. TIH with packer with 1.81" profile nipple and set packer at 12120'. TOOH with wireline. Bled well down - packer not holding. Setting tool has sand in it. Shut well in for night.

11-5-99 - Bled well down. Pumped 75 bbls 2% treated water. TIH with on/off tool, ported nipple and tubing. Tagged packer. Load and wash off top of packer. Released packer and TOOH. Shut well in.

Operations Technician November 8, 1999