Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CON

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

SERVATION DIVISION P.O. Box 2088 e, New Mexico 87504-2088	WELL API NO. 30-025-20388	
	5. Indicate Type of Lease STATE	FEE

Santa Fo 6. State Oil & Gas Lease No. DISTRICT III
1000 Rio Brazos Rd., Aziec, NM 87410 vo-5490 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Carper McAlester ATE State 1. Type of Well: GAS X OTHER WELL 8. Well No. 2. Name of Operator YATES PETROLEUM CORPORATION 9. Pool name or Wildcat Wildcat Mississippian 3. Address of Operator 105 South 4th St., Artesia, NM 88210 Line 4. Well Location Feet From The West _ Line and ____1650 : 660 Feet From The North I mit I etter .. **NMPM** 34E 11S Range Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) Section 4144' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: 11. NOTICE OF INTENTION TO: ALTERING CASING REMEDIAL WORK PLUG AND ABANDON PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. CHANGE PLANS

TEMPORARILY ABANDON CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** XX OTHER: Production casing & cement OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed TD 12342'. Reached TD at 1:15 AM 10-2-99. Ran 282 joints of 4-1/2" 11.6# 8rd S95 LT&C work) SEE RULE 1103. (12352.90') of casing set at 12342'. Float shoe set at 12342'. Float collar set at 12296'. Bottom marker set at 12100-12119'. Pumped 500 gallons of mud flush ahead of

500 sacks Interfill H, 1/4#/sack flocele and .4% Halad 322 (yield 2.76, weight 11.5). Tailed in with 300 sacks Super H, 5#/sack gilsonite, 1#/sack salt, .5% Halad 344, .4% CFR3 and .2% HR7 (yield 1.67, weight 13.0). PD 3:30 AM 10-4-99. Bumped plug to 2450 psi for 3 minutes, OK. WOC. Released rig at 7:30 AM 10-4-99. NOTE: Displaced with

191 bbls 2% KCL.

Waiting on completion unit.

I hereby certify that the information above is true indecomplete to the best of my knowledge and	obeid. Operations Technician	DATE Oct. 12, 1999
SIGNATURE Rusty Klein		TELEPHONE NO. 505/748-147
(This space for State Use) OFFICE ALSO AND		OCT & () 1998
π	T.B	DATE
APPROVED BY	•	