DISTRIBUTION SANTA FE U.S.G.S. LAND OFFICE OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DELIC ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. 1. OIL GAS WELL OTHER. Dry Hole 2. Name of Operator Ard Drilling Company 3. Address of Operator C/O Oil Reports & Gas Services, Box 763, Hobbs, New Mexico 4. Location of Well UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM THE WEST TOWNSHIP 9 S RANGE 35 E NMPM.		
U.S.G.S. LAND OFFICE OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO SEPERS OF PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO SEPERS OF PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO SEPERS OF PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR FROM FROM FOR PROPOSALS.) (A. LOCATION OF SEPERSON OF THE PROPOSALS.) (A. LOCATION OF WELL (A. LOCATIO	Form C-103 Supersedes Old C-102 and C-10. Effective 1-1-65)3
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPERTY OF PROPERTY. 1. OKAL	Indicate Type o	Fee .
10. OIL WELL OTHER. Dry Hole 2. Name of Operator 3. North Line and 660 FEET FROM THE North Line and 660 FEET FROM THE NORTH LINE AND 660 FEET FROM THE NORTH LINE, SECTION 32 TOWNSHIP 9 S RANGE 35 B NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4165 GK 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other I SUBSEQUENT RE PERFORM REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMERCE DRILLING OPHS. CASING TEST AND CEMENT JOB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimately work) SEE RULE 1103. To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cament. Shoot off 5 1/2" casing at 4783. Spot 40 sack plug across 5 1/2" casing stub, spot 40 sack plug across 5 1/2" casing stub, spot 40 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing sboe at 4061. Set 10 sack plug across 8 5/8" casing	State Oil & Gas K-3706	
OTHER. Dry Hole 2. Name of Operator Ard Drilling Company 3. Address of Operator C/O Oil Reports & Gas Services, Box 763, Hobbs, New Mexico 4. Location of Well UNIT LETTER D , 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 9 S RANGE 35 E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other I NOTICE OF INTENTION TO: SUBSEQUENT RE PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estim work) SEE RULE 1103. To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing stub, spot 40 sack plug across 5 1/2" casing stub, spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 5 1/2" casing shoe at 4061. Set	Unit Agreement	Name
2. Name of Operator Ard Drilling Company 3. Address of Operator C/O Oil Reports & Gas Services, Box 763, Hobbs, New Mexico 4. Location of Well UNIT LETTER D . 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 9 S RANGE 35 E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4165 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other I NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JQB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1103. To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing stub, spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 2 or 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 2 or		
2. Address of Operator C/O Oil Reports & Gas Services, Box 763, Hobbs, New Mexico 4. Location of Well UNIT LETTER D	Farm or Lease Nowe State Well No.	
A. Location of Well UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM THE THE West LINE, SECTION 32 TOWNSHIP 9 S RANGE 35 B NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other I NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CHANGE PLANS OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including esting work) SEE RULE 1103. To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing at 4783. Spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061.	1	
The West Line, section 32 Township 9 S RANGE 35 E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other I NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimwork) SEE RULE 1103. 18. Check Appropriate Box To Indicate Nature of Notice, Report or Other I SUBSEQUENT RE 19. Casing test and cement JQB OTHER 19. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimwork) SEE RULE 1103. 19. Confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing at 4783. Spot 40 sack plug across 5 1/2" casing stub, spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug across 8 5/8" casing shoe at 4061.	. Field and Pool des. Jenki	-
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Indicate Nature of Notice Nature of Na		
To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing stub, spot 40 sack plug at 258 casing shoe at 4061. Set 10 sack plug at 250 continue or Other Intervals approval to plug at 4783. Spot 40 sack plug at 250 casing shoe at 4061. Set 10 sack plug at 2 sacks plug at 358 casing shoe at 4061. Set 10 sack plug at 358 casing shoe at 4061. Set 10 sack plug at 350 casing shoe at 4061. Set 10 sack plug at 360 casing shoe at 4061. Set 10 sack plug at 360 casing shoe at 4061. Set 10 sack plug at 360 casing shoe at 4061. Set 10 sack plug at 360 casing shoe at 4061.		
Check Appropriate Box To Indicate Nature of Notice, Report or Other In Notice of Intention to: Perform remedial work	. County	
To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing at 4783. Spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at	ALTERIN Plug an	NG CASING
To confirm verbal approval to plug as follows: Set 5 1/2" cast iron bridge plug at 9750 and cap with 2 sacks cement. Shoot off 5 1/2" casing at 4783. Spot 40 sack plug across 5 1/2" casing stub, spot 40 sack plug across 8 5/8" casing shoe at 4061. Set 10 sack plug at	imated data of a	tarting any proposed
Clean and level location ready for inspection.		

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

Agent

DATE

7/31/68

CONDITIONS OF APPROVAL, IF ANY: