


R. 2631 East 4th St. N. E.
J. K. Blackman



LTR



Job separation sheet

-continued-

Cored 9708-50', rec 42' being: 3' sh., 2' ls., horiz. frags., 3½' dense shly ls., 2½' shale, 1' shly ls., 2½' dense ls., 3½' shale, 4½' dns ls., 2½' ls., fair to good vuggy PPP, NS, 6' ls., very good vuggy & PPP, NS, 11' dense ls., horiz. hairline frags.

DST 9718-9750' (Bough "C"), open 3 hrs, rec 6122' salt wtr, 180' salt wtr CDM, FP 91-2669#, 90" FSIP 3143#.

Cored 9750-9810', rec 60' being: 2' dense ls., 6½' sh., 23½' dns ls., 13' shly ls., 8' sh., 6' dense ls., 1' ls., fair PPP, NS.

Cored 9810-70', rec 60' being: 4½' ls., good vuggy & PPP, NS, 28' dns ls., 1½' sh., 7' ls., fair PPP, BO&G, 19' dense ls.

7-8-63

Drlg. 10407' ls.

DST 9820-70' (Cisco), open 1 hr, rec 5 gals DM, NS oil, wtr or gas, FP 61-61#, 90" FSIP 85#.

Cored 9870-9907', rec 37' being: 6' shale, 31' shly ls., NS.

7-15-63

Drlg. 10944' ls. & sh.

7-22-63

TD 11088' ls., fshg.

7-29-63

Drlg. 11716' ls. & sd.

8-5-63

Drlg. 12232' ls. & ch.

8-12-63

TD 12660', prep to DST 12628-660'.

Circ. samples @ 12610', 12638' & 12645'.

8-19-63

TD 12825' dolo. & ch., PB 12625', prep to run casing.

DST 12628-660', open 1 hr, used & rec 2800' WB, rec 30' DM, NS, FP 48-404#, 60" FSIP 1101#.

