

COUNTY	LEA	FIELD Wildcat	STATE	N.M.
WC OPR	FULTON, R. H.	MAP		
1 Flake, Myrtle L.		CO-ORD		
Sec. 17, T-9-S, R-36-E				
660' fr S & W Lines of Sec.				
Spud 11-14-62		CLASS E4085		
P & A 8-14-64		FORMATION	DATUM	FORMATION
CSG & SX - TUBING		SAMPLE:		
8 5/8" 271' 225		SA Porosity		
4 1/2" 4872' 150		4765		
LOG: Anhy		2170		
		Yates 6602 EVNT		
		SA 4040		
LOGS EL GR RA IND HC A				
		TD 4872'		

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4870'	TYPE
DATE			

F.R. 11-15-62
PD 4870' - SA
11-19-62 Drlg. 4092' 1m.
11-26-62 TD 4872', prep to perf.
Cored 4770-4821', rec 51' anhy dolo., w/scatt. BO.
Cored 4821-4872', rec 51' same.
12-13-62 NR
12-10-62 TD 4872', prep to perf.
12-17-62 TD 4872', SI.
Perf 4824-48' W/2 SPF
Ac. 2500 gals.
12-31-62 TD 4872', WO Pump.
1-7-63 TD 4872', WO Pump.
1-14-63 TD 4872', WO Pump.
1-21-63 TD 4872', WO Pump.
1-28-63 TD 4872', WO Pump.
2-4-63 TD 4872', WO Pump.
2-11-63 TD 4872', WO Pump.

3-25-63 TD 4872', prep to perf.
Swbd 100% salt wtr from perfs 4824-48'
Had communications
Squeezed perfs 4824-48' W/100 sx.
6-17-63 TD 4872', pmpg load.
Re-Perf 4824-30', 4834-37', 4840-48' W/2 SPF
Ac. 500 gals.
Re-Ac. 2000 gals. 4824-48'
Swbd salt wtr
Squeezed perfs 4824-48'.
Re-Perf 4825-27' W/2 SPF
Ac. 500 gals.
Re-Ac. 2500 gals. 4825-27'
Had communications
Squeezed perfs 4825-27'

Re-Perf 4825-28' W/2 SPF
Ac. 500 gals.
Re-Ac. 2500 gals.
Frac 20,000 gals oil + 30,000# sd. 4825-28'.
Pmpd 50 bbls fluid per day (5 BLO, 45 BW).
9-21-64 TD 4872', PLUGGED & ABANDONED.