

APPROVED

(SUBMIT IN TRIPLICATE)

Land Office

0308484

Lease No.

Unit

M

JUN 14 1963

UNITED STATES

DEPARTMENT OF THE INTERIOR

J. L. GORDON

GEOLOGICAL SURVEY

ACTING DISTRICT ENGINEER

JUN 14 1968

SUNDRY NOTICES AND REPORTS ON WELLS

SURVEY
HOBBES, NEW MEXICO

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	XX		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 11, 1963

Well No. 1 is located 660 ft. from ^(N)_S line and 510 ft. from ^(E)_W line of sec. 7

SW/4 Sec. 7

9-S

37-E

NMPM

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Allison Penn.

Roosevelt

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Federal-Sanchez #1: Drilled to TD of 9765', 7-7/8" hole. Cored from 9660-9732', top of Bough C at 9700'. No porosity, no shows. We propose to plug well as follows: 100' cement plug from 9665-9765; 100' cement plug from 4225-4325', 100' cement plug across stub of 8-5/8" casing. Approximate top of cement behind 8-5/8" casing which was set at 4275' is 3300', and an attempt will be made to recover 3300' of 8-5/8" casing. Cement plug of 100' will be placed across shoe of 13-3/8" casing at 335-443.35. Cement plug of 20 ax to be placed in top of 13-3/8" casing, with proper U.S.G.S. marker installed. Location to be cleaned up, pits leveled and made ready for inspection. Verbal permission obtained from Mr. Jack Gordon to plug as above. Hole will be filled with heavy mud between cement plugs.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Arnold H. Bruner**Address **W. Pickett****901 Midland Savings Bldg.****Midland, Texas**

By

Title

Agent