

20 425 - 10501

WC	COUNTY	LEA	FIELD	Wildcat	STATE	N.M.
OPR	COASTAL STATES GAS PRODUCING COMPANY					MAP
	1 Skelly-State					
	Sec. 21, T-9-S, R-33-E					CO-ORD
	1978' fr N Line & 1993' fr W Line of Sec.					
	Spud 9-10-63					CLASS
	Comp 2-24-64					EL 43752
			FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING			LOG:			
			Yates	2490		
13 3/8" 405' 350			SA	3677		
8 5/8" 4009' 900			Glor	5166		
5 1/2" 9407' 350			Clfk	5877		
			Tubb	6638		
LOGS EL GR RA IND HC A			Abo	7495		
			TD 9407', PBD 9300'			

IP San Andres Perfs 4502-18' Pmpd 47 BOPD + 67 BW. Pot. Based on 24 hr test, gravity 18.5.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Sealing Service, Inc.

CONT.	PROP DEPTH 9800'	TYPE RT
DATE		

F.R. 9-12-63; Oper's Elev. 4325' Df.
PD 9800' - Bough "C"

9-16-63 Drlg. 3850'.

9-30-63 TD 6313' lm. & sh., fshg.
DST 4472-4505', open 1 hr,
rec 180' gas in DP, 65' GCM + 2 gals oil,
30 min ISIP 1093#, FP 29-29#,
45 min FSIP 757#.

10-7-63 Drlg. 7677' lm. & sh.

10-14-63 Drlg. 8244'.

10-21-63 Coring @ 8556'.
Cored 8515-31', rec 16' dolo., sh. & anhy., NS.
Cored 8531-50', rec 18' anhy. & sh., NS.

10-28-63 Drlg. 8696'.
Cored 8550-63', rec 12' anhy. & sh., NS.
Cored 8563-82', rec 19' anhy., sh. & dolo., NS.
Cored 8582-8606', rec 24' sh., anhy. & dolo., w/
show oil 8605-06'.
Cored 8606-8653', rec 47' dolo. & lm., NS.

11-4-63 Drlg. 9289'.

11-11-63 TD 9407', prep to test.
Perf @ 9356', 9361', 9363' W/1 SPI
Perf 9370-74' W/2 SPF
11-18-63 TD 9407', PBD 9390', RU Pump.
Ac. 500 gals (MA) (9356-74')
Swbd 90 BW + 50 BO in 24 hrs.
11-26-63 TD 9407', PBD 9390', prep to test on pump.
12-2-63 TD 9407', PBD 9390', tstg. on pump.
Pmpd 18 BO + 90 BW/18 hrs.
12-9-63 TD 9407', PBD 9390', tstg. on pump.
Pmpd 170 BW + 1 BO/24 hrs.
12-16-63 TD 9407', PBD 9390', tstg. on pump.
Pmpd 3 BO + 50 BW/24 hrs.
12-30-63 TD 9407', PBD 9390', SD Pump repairs.
Pmpd 2 BO + 40 BW/24 hrs.
1-6-64 TD 9407', PBD 9390', tstg on pump.

pmpd 1 BO + 20 BW/24 hrs.
1-13-64 TD 9407', PBD 9390', SI.
1-20-64 TD 9407', PBD 9390', SI.
1-27-64 TD 9407', PBD 9390', SI.
2-3-64 TD 9407', PBD 9390', SI.
2-10-64 TD 9407', PBD 9390', SI.
2-17-64 TD 9407', PBD 9390', prep to PB & test SA.
2-24-64 TD 9407', PBD 9300', WOO.
PB to 9300'
Perf (San Andres) 4502-18' W/2 SPF
Ac. 1000 gals.
had communications; swbd & flwd salt wtr, w/
tr. of oil.
3-2-64 TD 9407', PBD 9300', RU Pump.
Swbd 47 BO + 65 BW in 24 hrs.
3-9-64 TD 9407', PBD 9300', RU Pump.
3-16-64 TD 9407', PBD 9300', WO NMOCC Potential.