

RECORD OF DRILL-STEM AND SPECIAL /TS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 9715 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 1/25, 1964
OIL WELL: The production during the first 24 hours was 80 barrels of liquid of which was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy	2070		T. Devonian		T. Ojo Alamo
T. Salt	2146		T. Silurian		T. Kirtland-Fruitland
B. Salt	2600		T. Montoya		T. Farmington
T. Yates	2660		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	3086		T. Granite		T. Dakota
T. Glorieta	3320		T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo	7674		T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	300	300	Sand & shale				
300	2070	1770	Red beds				
2070	2146	76	Anhydrite				
2146	2600	514	Salt & anhydrite				
2600	3086	1236	Sand, anhy., shale stringers				
3086	3320	1434	Dolomite				
3320	7674	2354	Sand, dol., shale				
7674	8803	1129	Shale & dolomite				
8803	9715	912	Lime & shale				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED