

COUNTY	LEA	FIELD	Lane, South	STATE	NM
OPR	BOREN, SAM & MAJOR & GIEBEL OILS				MAP
	3 Humble-State "C"				
	Sec. 34, T-10-S, R-33-E				CO-ORD
	660' fr N Line & 1980' fr E Line of Sec.				
	Spud 10-14-64				EL 4199'
	Comp 12-15-64	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Rust	1900		
		Yates	2588		
		SA	3845		
		Tubb	6761		
		Abo	7598		
		Wolfc	8798		
		Bo "C"	9663		
LOGS	EL	GR	RA	IND	HC A
		TD 9800', PED 9795'			

IP Bough "C" Perfs 9670-78' Flwd 210 BOPD + 100 BW. Pot. Based on 24 hr test thru 24/64" chk., TP 80#, CP Pkr, gravity 47.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Hissom Drlg. Co.	PROP DEPTH	9900'	TYPE
DATE				

F.R. 10-15-64; Oper's Elev. 4199' KB
PD 9900' - Bough "C"
Contractor - Hissom Drlg. Co.
10-19-64 TD 1825', WOC.
10-26-64 TD 4039', WOC.
11-2-64 Drlg. 5358' say 1m.
11-9-64 Drlg. 7205' 1m.
11-16-64 Drlg. 8327' 1m. & sh.
11-23-64 Drlg. 9043' 1m.
11-30-64 Drlg. 9576'.
DST 9071-80', open 1 hr,
Rec 420' Salt Wtr,
30 min ISIP 300#, FP C-350#,
1 hr FSIP 2250#.
12-7-64 TD 9800', WOC.
DST 9751-61', open 1 hr,
Rec 210' DM,
All pressures 0.

12-7-64 - cont. -
SP DST 9671-81', open 1 hr,
GTS 4 mins, MTS 35 mins, OTS 42 mins,
Flwd est 1.5-2 MMCFGPD, w/spray of oil,
Rec 1000' oil + 500 Salt Wtr,
30 min ISIP 2380#, FP 450-1450#,
1 hr FSIP 2290#.
12-14-64 TD 9800', prep to perf.
12-21-64 TD 9800', PED 9795', COMPLETED.
Perf 9670-78' W/4 SPF
Ac. 1000 gals.