

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-20618
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-9948
7. Lease Name or Unit Agreement Name SOLDIER HILL AE STATE
8. Well No. 1
9. Pool name or Wildcat Caprock Devonian East

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>	RECEIVED APR 24 1989
2. Name of Operator Wagner & Brown	OIL CONSERVATION DIV. SANTA FE
3. Address of Operator P.O. Box 1714, Midland, TX 79702	
4. Well Location Unit Letter C : 800 Feet From The North Line and 1800 Feet From The West Line Section 23 Township 12S Range 32E NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4336 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1) Set EZSV @ 9000'. Pmp 1000' of Class "H" cmt (114 sx yield 1.18)

2) Spot cmt plugs as follows:

6400'	25 sx
5050'	25 sx
4350'	35 sx

3) Cut 5-1/2" csg @ 3670' and POOH.

4) Spot cmt plug 3720-3620' w/ 50 sx.

5) Spot cmt plug 1100'-1000' w/ 50 sx.

6) Set 10 sx plug at surface, weld on plate and install dryhole marker.

PERF 8 5/8 CSG @ 400' & SQUEEZE PERF

Plugging operations to begin upon approval from Commission.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Drew Diggins TITLE Petroleum Engineer DATE 4/13/89

TYPE OR PRINT NAME Drew Diggins TELEPHONE NO. (915) 686-59

(This space for State Use)

APPROVED BY Paul Kautz TITLE Geologist DATE APR 28 1989

CONDITIONS OF APPROVAL, IF ANY: