

COUNTY	LEA	FIELD	Mescalero-San Andres	STATE	N.M.
OPR	CITIES SERVICE OIL COMPANY				MAP
6 State "AD"					
Sec. 22, T-10-S, R-32-E					CO-ORD
1980' fr N Line & 330' fr E Line of Sec.					
Spud 7-20-64				CLASS	EL 4332
Comp 8-23-64		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
8 5/8"	397'	325	Yates 2223'		
4 1/2"	4448'	250	Queen 2862		
		SA 3422			
		Slaughter			
		4046			
LOGS EL GR RA IND HC A		TD 4450', PBD 4397'			

IP San Andres Perfs 4077-4155' Pmpd 70 BOPD + 12 BW. Pot.
Based on 24 hr test, gravity 15., GOR 214.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4450'	TYPE
DATE			

F. R. 7-9-64.
PD 4450' - San Andres.
7-27-64 Drlg. 3535' dolo.
8-3-64 TD 4450', prep to run logs.
Cored 4070-4128', rec. 55' dolo., fractured
w/good poro. & bldg. oil throughout.
Cored 4128-58', rec. 30' dolo w/scatt. bldg.
oil from fracs. & spotty PPP.
Cored 4158-88', rec. 28' being:
5' dolo w/bldg. oil from fracs & PPP; 23'
dolomitic limestone, w/sli bldg. oil from fracs.
8-10-64 TD 4450', swbg.
Perf. @ 4077', 4080', 4083', 4088', 4091', 4094',
w/1 SPI.
Ac. 1000 gals.
Swbd. 26 BNO + 23 BLW/8 hrs.
Re-Ac. 1000 gals.

- cont'd -

8-10-64 - cont'd -
 Swbd. 45 BNO + 29 BLW/4 hrs. 20 mins.
8-17-64 TD 4450', tstg. on pump.
 Ppd. 38.7 BO + 93 BW/48 hrs.
8-24-64 TD 4450', PBD 4397', COMPLETED.
 Set Pkr @ 4100'
 Perf @ 4113', 4133', 4143', 4155' W/4 SPI
 Ac. 500gals 4113-4155'
 Swbd dry.
 Re-Ac. 2500 gals. 4113-4155'
 Re-Ac. 2500 gals. 4113-4155'
 Swbd 36 BO + 2 BW/no time.
 Pulled Pkr @ 4100'.