

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-7392
7. Lease Name or Unit Agreement Name Flying "M" (SA) Unit Tr 13
8. Well No. 5
9. Pool name or Wildcat Flying "M" San Andres

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Water Injection Well	
2. Name of Operator Coastal Oil & Gas Corporation	
3. Address of Operator 211 N. Robinson, Suite 1700, Oklahoma City, OK 73102	
4. Well Location Unit Letter F : 1980 Feet From The North Line and 1993 Feet From The West Line Section 20 Township 9-S Range 33-E NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4374' G.L.	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. On January 11, 1983, this well was partially plugged and temporarily abandoned (See C-103 dated 8-30-83, attached). P&A proposal as follows:

1. GIH with workstring to 4237'. Circulate hole with 9.5 ppg mud. POOH with workstring.
2. GIH with perf gun & shoot 4 holes @1990' (T/Salt@1940') & 4 holes @312' (surface csg @262').
3. PU retainer & GIH to 1890'. Squeeze below retainer w/50sx Class "C". This represents 100' of fillup in the annulus(150%excess) & 100' of fillup in the 4½" csg between the retainer & per
4. POOH. PU retainer & GIH to 212'. Squeeze below retainer w/50sx Class "C". This represents 100' of fillup in the annulus(150%excess) & 100' of fillup in the 4½" csg between the retainer & perfs.
5. POOH. Spot 10sx of Class "C" inside 4½" & 8-5/8" csg from 30' to surface.
6. Cut off both casings 3' below ground level.
7. Install P&A marker, clean and restore location.

ALL COMMENTS MUST BE NOTED 24
HOURS AFTER THE BEGINNING OF
SUCCEEDING OPERATIONS FOR THE C-103
TO BE APPLIED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Clarence T. Miller TITLE Sr. Petroelum Engineer DATE 2/28/92
(405)
TYPE OR PRINT NAME Clarence T. Miller TELEPHONE NO. 239-7031

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 09 '92