

COUNTY	LEA	FIELD Wildcat	STATE N.M.
WC OPR	FULLER, W. M. & A. P.		MAP
1 Six, Grover C.			
Sec. 30, T-11-S, R-38-E			CO-ORD
1980' fr S Line & 660' fr W Line of Sec.			
Spud 2-10-64		CLASS	EL 3918 5
P & A 5-13-64		FORMATION	DATUM
CSG & SX . TUBING		LOG:	
8 5/8"	359'	250	Yates 3040
5 1/2"	5164'	200	SA 4407
		SA Porosity	
		5111	
LOGS EL GR RA IND HC A			
		TD 5164'	

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 5500'	TYPE
DATE		

	F.R. 2-13-64
	PD 5500' - SA
2-17-64	Drlg. 4532'.
2-24-64	TD 5164', running 5½" casing
	Cored 5111-15', rec 4' dolo., w/scatt. show
	Cored 5115-36', rec 19' dolo., w/show throughout
	DST 5100-36', open 1 hr 30 mins,
	Rec 15' drlg. fluid
	1 hr ISIP 135#, FP 60-75#,
	1 hr FSIP 150#.
	Cored 5136-64', rec 28' dolo., w/show throughout
	DST 5132-64', open 1 hr 30 mins,
	Rec 150' HG&OCM, 150' HG&HOCM + 20' sul. wtr,
	1 hr ISIP 1906#, FP 19-209#, 1 hr FSIP 1620#.
3-2-64	TD 5164', tight
3-9-64	TD 5164', tight
3-16-64	TD 5164', tight
3-23-64	TD 5164', tight
4-6-64	TD 5164', tight
4-20-64	TD 5164', prep to P&A.

LEA Wildcat N.M. Sec. 30-11S-38E
FULLER, W.M. & A.P. #1 Six, Grover C. Page #2

4-20-64 - cont'd -
Perf. @ 5110', 5120', 5130', 5135', 5140',
& 5148' w/2 SPI.
Ac. 2000 gals. (MA).
Frac. 20,000 gals. oil + 20,000# sd.
Rec. load.
Swbd. 100% sul. wtr.
5-25-64 TD 5164', PLUGGED & ABANDONED.