

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

~~69~~-NM-0152965

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir
Use APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

J. C. BARNES OIL CO.

3. ADDRESS OF OPERATOR

P.O. BOX-505, MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below)
At surface

740°N - 571°E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SOUTHERN NAT. GAS FED.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

INBE (N. PENN.)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 1, 11-S 33-E

12. COUNTY OR PARISH

LEA

13. STATE
NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

? PURCH. FROM PUBCO

4190' GL.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per
nent to this work.) *

PREP. TO PLUG & ABANDON ON OR ABOUT AUGUST 25, 1972:

1. PROPOSE TO SET A CIBP WITH 20' CEMENT AT 9000'.
2. PROPOSE TO SPOT A 25 SX CEMENT PLUG AT 4 1/2" CASING STUB AT 6000'.
3. PROPOSE TO SPOT A 25 SX CEMENT PLUG AT TOP OF GLORIETTA AT 5290'.
4. PROPOSE TO SPOT A 25 SX CEMENT PLUG AT 7 5/8" CASING SHOE AT 4000'.
5. PROPOSE TO SPOT A 25 SX CEMENT PLUG AT 7 5/8" CASING STUB AT 2000'.
6. PROPOSE TO SPOT A 25 SX CEMENT PLUG AT 10 3/4" CASING SHOE AT 1860'.
7. PROPOSE TO SPOT A 10 SX CEMENT PLUG AT SURFACE WITH MARKER.
8. HOLE WILL BE LOADED WITH MUD-LADEN FLUIDS.

AMENDMENT:

- (a) Cap CIBP in No. 1 above with 35 feet of cement rather than 20 feet.
- (b) All other cement plugs to be minimum of 100 feet in length.
- (c) If 4 1/2" casing is not pulled from below 4026 feet, contact U.S.G.S.
before proceeding further.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE PRODUCTION ACCT.

TITLE

DATE 8-17-72

DATE

APPROVED
AS AMENDED
AUG 22 1972
ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side