

IP SA Perfs 4418-22' Pmpd 33 BOPD + 49 BW. Pot. Based on 24 hr test, gravity 19.4, GOR 407.

CONT.	PROP DEPTH 4500'	TYPE
DATE		

F. R. 12-10-64; Oper's Elev. 4393'.
PD 4500' - San Andres.
12-8-64 Drlg. 3696'.
12-14-64 TD 4550', prep to run csg.
Cored 4405-24', rec. 17' being: 8½' dolo.
W/NS, 7' dolo W/fair poro. BO, good stn. & odor,
1½' dolo W/NS.
Cored 4424-74', rec. 50' being:
36' dolo W/scatt. poor poro. BO, good stn. &
odor, 14' dolo W/NS.
12-21-64 TD 4550', PBD 4482', prep to re-perf.
Perf. 4418-24' W/1 SPF.
Ac. 250 gals.
Swbd. 42 BO + 6 BAW/no time.
Re-Ac. 1000 gals. 4418-24'.
Swbd. 54 BO + 26 BAW/7 hrs.
Swbd. 47 BW/5½ hrs.
Squeezed perfs. 4418-24' W/121 sx.

LEA COUNTY Flying 'M'-SA NM
SHELL OIL COMPANY, #3 State FMB

Sec. 17-9S-33E
Page #2

1-4-65 TD 4550', PBD 4482', COMPLETED.
Re-Perf 4418-22' W/3 SPF
Ac. 500 gals.
Swbd 67 BO in 4 hrs.
Re-Ac. 1000 gals. 4418-22'.

COUNTY	LEA	FIELD	Flying "M"	STATE	NM	OWWO
OPR	COASTAL STATES GAS PRODUCING CO.			MAP		
WI-3 Flying M (SA) Unit Tr. 3						
Sec. 17, T-9-S, R-33-E						
1980' FNL, 1980' FWL of Sec.						
Re-Spd 12-8-66						
Re-Cmp 1-1-67						
		CLASS		OWIDE EL [REDACTED]		
		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
8 5/8" 400' 250						
4 1/2" 4549' 200						
LOGS EL GR RA IND HC A						
		TD 4550', PBD 4482'				
SA Perfs 4418-4465' - WATER INJECTION WELL						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	TYPE	WO
DATE			

F.R.C. 10-19-67; OWWO
 (Orig. Shell Oil Co., #3 State FMB; Cmp
 1-1-65 from SA Perfs 4418-22', OTD 4550',
 OPB 4482'.) Elev. 4393' DF, Orig.
 10-16-67 TD 4550', PBD 4482', COMPLETE
 Perf 4430-65' W/1 SPF
 Acid (4430-65') 5000 gals