

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy 2184 T. Canyon _____
T. Salt 2260 T. Strawn _____
B. Salt 2810 T. Atoka 11402
T. Yates 2848 T. Miss 11650 (Lower)
T. 7 Rivers _____ T. Devonian 12258
T. Queen _____ T. Silurian _____
T. Grayburg _____ T. Montoya _____
T. San Andres 4198 T. Simpson _____
T. Glorieta 5560 T. McKee _____
T. Paddock _____ T. Ellenburger _____
T. Blinberry _____ T. Gr. Wash _____
T. Tubb 6955 T. Granite _____
T. Drinkard _____ T. Delaware Sand _____
T. Abo 8137 T. Bone Springs _____
T. Wolfcamp _____ T. _____
T. Penn. 9455 T. _____
T. Cisco (Bough C) 9800 T. _____

Northwestern New Mexico

T. Ojo Alamo _____ T. Penn. "B" _____
T. Kirtland-Fruitland _____ T. Penn. "C" _____
T. Pictured Cliffs _____ T. Penn. "D" _____
T. Cliff House _____ T. Leadville _____
T. Menefee _____ T. Madison _____
T. Point Lookout _____ T. Elbert _____
T. Mancos _____ T. McCracken _____
T. Gallup _____ T. Ignacio Qtzte _____
Base Greenhorn _____ T. Granite _____
T. Dakota _____ T. _____
T. Morrison _____ T. _____
T. Todilto _____ T. _____
T. Entrada _____ T. _____
T. Wingate _____ T. _____
T. Chinle _____ T. _____
T. Permian _____ T. _____
T. Penn. "A" _____ T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	295	295	Surface Soil & Shale	Drill Stem Test			
295	1905	1610	R. Bed-Shale	From 12,153-12,295 TD. Opened w/good bl			
1905	2184	279	Sand-Shale	decreasing to poor, died in 40 min.			
2184	2260	76	Anhydrite	Tool left open 13 hrs - Took 45 min SIP			
2260	2810	550	Salt-Anhy-Gyp	Rec. 9384' fluid, 1288' Oil & Mud Cut			
2810	4198	1388	Broken Anhy-Shale-Sand	water blanket, 5888' drlg mud, 1012'			
4198	5560	1362	Dolo. w/Anhy stringers	salty muddy salt water, 1196' Oil & Gas			
5560	6955	1395	Lime & Snd	Cut Salt Water. Hyd. in and out 5067#			
6955	8137	1182	XXXXX Sh-Lime-Anhy	ISIP 5067, IFP 4897, FFP 4897,			
8137	9455	1318	Gr. Shale-Lime-Anhy	FSIP 4897#.			
9455	9845	390	Red & Gr. Shale-L-Anhy	Plugged & Abandoned as follows:			
9845	11402	1557	L-Black Shale	100 sx @ 10,000; 25 sx @ 8950; 25 sx @			
11402	11650	248	Sand-Lime-Shale	7740; 25 sx @ 5570; 25 sx @ 4240. Shot			
11650	12176	526	Lime-Chert	off 8 5/8, rec. 1200', left remainder in			
12176	12258	82	Brown Woodford Shale	hole; spotted 25 sx at 1250-1150; 25 sx			
12258	12295	37	Cherty Lime & Dolo.	@ 324', 10 sx @ surface. Set regula-			
Total	Depth	12295		tion marker.			