

COUNTY LEA FIELD Sawyer STATE NM
 OPR SOCONY MOBIL OIL CO., INC. MAP
1 McCormick-Federal "B"
Sec. 29, T-9-S, R-38-E CO-ORD
660' fr S & W Lines of Sec.
Spud 1-20-65 CLASS EL 3945'

Comp 2-12-65	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING LOG: 8 5/8" 360' 350 4 1/2" 3070' 250	SA 4178			
	SA Porosity			
	4889			
4045' 2-20-65, 109 HC *				
	TD 5070' PBD 5033'			

1" Gas - 4923-79' Flwd 327 MCFGPD + 18 BO & 24 BW.
 Pot. Bal. on 24 hr test thru 48/64" chk., TP 422#, gravity
 oil 42.5, WGR 5600.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton Drlg. Co. PROF DEPTH 5100' TYPE
 DATE

1-21-65; Oper's Elev. 3945' Df
 PD 5100' - SA
 Contractor - Sitton & Norton Drlg. Co.
 1-25-65 Drlg. 920'.
 2-1-65 Drlg. 4900'.
 2-9-65 TD 5070', PBD 5033', swbg load.
 Perf @ 4923', 4925', 4929', 4931', 4939',
 4941', 4943', 4947', 4949', 4957', 4961',
 4963', 4965', 4969', 4973', 4975', 4977',
 4979' W/1 SPI
 1000 gals.
 Flow gas @ rate of 259 MCFGPD, no fluid, for
 24 hrs thru 48/64" chk., TP 400#.
 4923-79' 5000 gals.
 10 BLO + 33 BAW (-82 BLO, 87 BAW)
 2-15-65 TD 5070', PBD 5033', tstg.
 Flwd 12 BNG + 24 B Salt Wtr in 24 hrs,
 gas volume 734 MCFGPD, TP 380#, GOR 65,333.
 2-17-65 TD 5070', PBD 5033', COMPLETED.