

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

| |
|---|
| WELL API NO. 30-025-21163 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. 058 102 |
| 7. Lease Name or Unit Agreement Name Flying "M" Unit Tract 13 |
| 8. Well No. 4 |
| 9. Pool name or Wildcat Flying "M" (SA) |

| | |
|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| 1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER | |
| 2. Name of Operator Coastal Oil & Gas Corporation | |
| 3. Address of Operator P. O. Box 235, Midland, Texas 79702 | |
| 4. Well Location Unit Letter <u>B</u> : <u>1983</u> Feet From The <u>East</u> Line and <u>660</u> Feet From The <u>North</u> Line Section <u>20</u> Township <u>9S</u> Range <u>33E</u> NMPM Lea County | |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) Gr 4372' | |

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set CIBP at 4336' (Perfs 4386-4425').
2. Circ hole with 9.5 PPG mud.
3. Spot 50' plug on top of CIBP (5 sacks). POOH with tbg.
4. Perf squeeze holes at 1900' and 320'.
5. GIH with cement retainer, set retainer at 1850'. Squeeze below retainer with 30 sacks. POOH with tbg.
6. Establish circ down 4-1/2" casing, through squeeze holes at 320' and back to surface through annulus.
7. Mix and pump 125 sacks cmt, circ cmt to surface.
8. Install P&A marker. Clean and level location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bobby L. Smith TITLE Sr. Petroleum Engineer DATE 2-24-94

TYPE OR PRINT NAME Bobby L. Smith TELEPHONE NO. 915 682-7925

(This space for State Use) **ORIGINAL SIGNED BY JERRY SEXTON**
DISTRICT I SUPERVISOR

FEB 28 1994

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: