

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-060581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. T. Caudle

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Bagley - Penn.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T12S, R33E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ TA

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer D, Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4258' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

December 19, 1983 to December 29, 1983 - Ran 4-5/8" bit on 2-3/8" tbq. & checked CI bridge plug at 8950'. Ran pkr. & tbq. & set pkr. at 8940'. Loaded tbq. & pressured up on bridge plug to 1000#. Held OK. Re-set pkr. at 8574', loaded annulus with produced water & pressured to 500#. Held OK. Dumped 5 sks. cement on top of bridge plug at 8950'. Estimated top of cement at 8900'. Set Baker CI bridge plug in 5-1/2" csg. at 8345' & dumped 2 sks. cement on top of bridge plug. Estimated top of cement at 8325'. Loaded 8-5/8" & 5-1/2" csg. w/produced water & pressured to 700#. Held OK. Testing procedure witnessed by Walter Cox w/BLM.

18. I hereby certify that the foregoing is true and correct

SIGNED

EB Disher

TITLE

Supv. Adm. Ser.

DATE

1-4-84

(This space for Federal or State office use)

APPROVED BY

GWO

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 9 1984

*See Instructions on Reverse Side

Carlsbad, NEW MEXICO

RECEIVED
MAY 11 1984
O.C.D.
HOBBS OFFICE