

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1705.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1580	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2193	T. Aloka	T. Pictured Cliffs	T. Penn. "D"
T. Yates		T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	2856	T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	3426	T. Montoya	T. Mancos	T. McCracken
T. San Andres		T. Simpson	T. Gallup	T. Ignacio Qizte
T. Gloria		T. McKee	T. Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T. T.
T. Blinberry		T. Gr. Wash	T. Morrison	T. T.
T. Tubb		T. Granite	T. Todillo	T. T.
T. Drinkard		T. Delaware Sand	T. Entrada	T. T.
T. Abo		T. Bone Springs	T. Wingate	T. T.
T. Wolfcamp		T. T.	T. Chinle	T. T.
T. Penn.		T. T.	T. Permian	T. T.
T. Cisco (Bough C)		T. T.	T. Penn. "A"	T. T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	334	334	Sand & Red Bed				
1235	1544	309	Red Bed & Anhydrite				
1544	1646	102	Anhydrite				
1646	3000	1354	Anhydrite & Salt				
3000	3382	382	Anhydrite				
3382	3482	100	Shale				
3482	3900	418	Shale				
3900	4040	140	Dolomite				
4040	4147	107	Dolomite				
4147	4190	43	Shale				
4190	4400	210	Shale				