

COUNTY	LEA	FIELD Flying "M"-Penn.	STATE NM
OPR	COASTAL STATES GAS PRODUCING CO.		MAP
4-16 Southern Minerals-State			
Sec. 16, T-9-S, R-33-E		CO-ORD	
659' fr S Line & 664' fr W Line of Sec.			
Spud 1-20-65		CLASS	
Comp 4-5-65		E	
		FORMATION	DATUM
CSG & SX - TUBING		LOG:	
13 3/8" 340' 350		Bough "C"	
8 5/8" 4599' 350		9250'	
4 1/2" 9401'			
LOGS EL GR RA IND HC A			
		TD 9401'	

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH 9500'	TYPE
DATE		

F.R. 1-21-65
 PD 9500' - Bough "C"
 Contractor - Cactus Drlg. Co.
 1-25-65 Drlg. 2840' anhy & salt.
 2-1-65 Drlg. 4325' 1m.
 2-8-65 Drlg. 4996' 1m.
 2-15-65 Drlg. 7330'.
 2-22-65 Drlg. 8330' 1m.
 3-1-65 Drlg. 8873' 1m.
 3-9-65 TD 9401', running logs.
 DST 9350-71', open 1 hr,
 rec 5' drlg fluid
 1 hr ISIP 44#, FP 44-44#, 1 hr FSIP 44#.
 3-15-65 TD 9401', WOC.
 SP DST 9250-76', open 1 hr 30 mins,
 GTS 2 mins, spray oil 20 mins,
 rec 4600' fluid (70% oil, 30% wtr)

5-65 - cont. -
1 hr ISIP 2850#, FP 374-1439#,
1 hr FSIP 2714#.
3-22-65 TD 9401', SI.
Perf 9253-63' W/4 SPF
Ac. 500 gals.
Swbd 15 BFPH (1-5% oil),
squeezed perfs 9253-63' W/100 sx.
Perf @ 9249' W/2 shots
Ac. 250 gals.,
failed to break.
Ac. 500 gals.,
could not break perf @ 9249'
Squeezed perf @ 9249' W/100 sx.

Re-Perf 9257-65' W/4 SPF
Ac. 250 gals.
swbd load.
Re-Ac. 250 gals. 9257-65'
4-5-65 TD 9401', TEMPORARILY ABANDONED.
Swbd 101 BF (5% oil, 95% wtr) in 6 hrs.
4-12-65 TD 9401', Completion Reported.