

This form is to be filled with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INSTRUCTIONS

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Albany	1445	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	1510	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2270	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates		T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	3028	T. Devonian	T. Menefee	T. Madison
T. Queen	3347	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	3630	T. Montoya	T. Mancos	T. McCracken
T. San Andres	5470	T. Simpson	T. Gallup	T. Ignacio Qizte
T. Glorieta		T. McKee	T. Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	
T. Blinberry	6535	T. Gr. Wash	T. Morrison	
T. Tubb		T. Granite	T. Todillo	
T. Drinkard	7250	T. Delaware Sand	T. Entrada	
T. Abo	8420	T. Bone Springs	T. Wingate	
T. Wolfcamp			T. Chinle	
T. Penn.			T. Permian	
T. Cisco (Bough C)			T. Penn. "A"	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness In Feet	Formation	From	To	Thickness In Feet	Formation
0	1450	1450	Red Beds				
1450	2270	2405	Salt Anhy.				
2270	2405	3028	Red sand and Shl.				
2405	3028	3350	Anhy, red sand & Shl.				
3028	3350	3350	Sand, Shl. & Anhy.				
3350	5470	5470	Dolo., Anhy., Shl.				
5470	5500	5500	Dolo. & Sand				
5500	7250	7250	Dolo., Lime & Shl.				
7250	8400	8400	Red & green shl., dolo.				
8400	9000	9000	Lime and Shl.				
9000	10,100	10,100	Lime & Shl.				
10,100	11,100	11,100	Lime sand and Shl.				
11,100	12,000	12,000	Lime chert & Shl.				
12,000	12,047	12,047	Dolomite				

DST Depth Open FP ISIP FSIP Recovered

1	4097-4185	48	70-94	422/31'	281/30'	60' DM	90' HGM, 130 O&G,	120' O&G	180' DM, 180 SWCIM	33' DM	900' Gas, 180' OIL,	900' HOGCM	390' MCSW, 1810' SW	Packer failed
2	8685-8719	1:45	45-140	1988/30'	1759/60'									
3	Mistun	2:05	278-1454	3383/30'	3248/60'									
4	10,535-65	2:00	46-46	46/30'	46/30'									
5	11,717-45	2:20	117-200	3573/30'	2944/60'									
6	11,970-12,017	2:20	117-200	3573/30'	2944/60'									
7	12,022-47	2:0	46-392	4575/30'	4575/30'	45								
8	11,002-11,115	8	256	4357/30'	4357/30'	-0-								