

COUNTY	LEA	FIELD	Mescalero-SA	STATE	N.M.
OPR	HUMBLE OIL & REFG. COMPANY				MAP
4 New Mexico State "AF"				API 30-025 21270	
Sec. 26, T-10-S, R-32-E				CO-ORD	
2310' fr S Line & 330' fr W Line of Sec.					
Spud 3-7-65					
Comp 5-8-65		CLASS		E	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
8 5/8"	1590'	700	Rust 1593		
4 1/2"	4400'	400	Yates 2228?		
			Queen 2901		
			SA 3462		
LOGS EL GR RA IND HC A					
		TD 4400'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4400'	TYPE
DATE			

F. R. 3-4-65; Oper's Elev. 4329' DF.
FD 4400' - San Andres.
Drlg. 1275'.
3-8-65 TD 4400', rung. logs.
3-15-65 TD 4400', PB 4368', swbg.
3-22-65 Perf. @ 4134', 4136', 4146', 4150', 4184', 4186',
W/1 SPF.
Ac. 250 gals.
Swbd. 40 BLO + 4 BAW.
Re-Ac. 5000 gals. 4134-86'
Swbd. 25 BLO + 82 BAW + 20 BFW/10 hrs.,
Swbd. 8 BLO + 88 BW/10 hrs.
3-29-65 TD 4400', PBD 4368', pmpg. load.
Pmpd. 120 BW, no oil, in 24 hrs. (~6 BLO).
4-5-65 TD 4400', PB 4368', tstg. on pump.
Pmpd. 27 BO + 354 BW/72 hrs.

4-12-65 TD 4400', PB 4368', tstg. on pump.
 Pmpd. 9 BO + 114 BW/24 hrs.
[REDACTED] 19-65 TD 4400', PB 4368', tstg. on pump.
 Pmpd. 4 BO + 114 BW/24 hrs.
4-26-65 TD 4400', PB 4368', swbg.
 Perf. @ 4324', 4326', 4332', 4338', 4341', 4342',
 4343' w/1 SPI.
 Set Pkr. @ 4295.
 Ac. 500 gals., swbd. dry.
 Re-Ac. 3000 gals. 4324-43'.
 Swbd. 85 BL & AW/8 hrs.
5-3-65 TD 4400', PB 4368', prep to P&A.
5-10-65 TD 4400', PBD 4368', PLUGGED & ABANDONED.

Memo

From

To Mr. L. L. Smith
Director
Bureau of the Census

4/26/65