

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
N.M. 0450847

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Am American Petroleum Corp.

3. ADDRESS OF OPERATOR

Box 68, Hobbs, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2300' FSL x 990' FWL, Sec. 13, (UNIT L, NW1/4 SW1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4128' R.D.B.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL "A"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

13-S-35 N.M.P.M.

12. COUNTY OR PARISH

13. STATE

LEA

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD-11940'. Ram Log. On 4-20-65, 7" OD 23-24' N-80 LTC & BT Casing was set at 11,940' w/1300sx. Slo-Set w/3/4" CFR-2/5x x 1/4" Tuf Plug 1/5x in first 500 ft. Top. cement 7602'. Tested casing w/ 1500 psi for 30 minutes. Test O.K. Core 6" hole 11940 - 11991 (TD) Perforated Beugh C 9550'-60 w/2SPF. Acidized w/500 gal PT FFW. 157 BO x 46 BW 24 hr. TPF 425, 14/64" CH, GOR 1120, Cgr 47.5'. Devonian open hole stimulated w/500 gal acid. (11940-991) PTF 434 BO x 55 BW 24 hrs. 14/64" CH, TPF 280, GOR 57, Cgr 43.8

18. I hereby certify that the foregoing is true and correct

SIGNED

G. R. WILLIAMS, JR.

TITLE

Area Foreman

DATE

5-4-65

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

MAY 5 1965

**J. L. GORDON
ACTING DISTRICT ENGINEER**

*See instructions on Reverse Side

(047)
044-1565
1-1608
1-505P
1-1615