

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 10 11 03 AM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 00 961

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Pubco Petroleum Corporation	8. Farm or Lease Name Humble "CC" State
3. Address of Operator P. O. Box 1419, Albuquerque, New Mexico	9. Well No. #7
4. Location of Well UNIT LETTER E 2086 FEET FROM THE North LINE AND 766 FEET FROM THE West LINE, SECTION 34 TOWNSHIP 108 RANGE 33E NMPM.	10. Field and Pool, or Wildcat So. Lane
15. Elevation (Show whether DF, RT, GR, etc.) 4200 GR (Est.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-1-65 Drilled 20" hole to 35 ft. Set 1 joint of 16" casing at 30 ft. Cemented to surface with 3 yards of ready mix.

9-1-65 Drilled 13 3/4" hole to 1810. Set 56 joints of 10 3/4", 32.75#, #40 casing at 1808. Cemented w/500 sx 50-50 Pozmix, 8% gel, and 200 sx. 50-50 Pozmix, 2% gel. Circulated 75 sx. WOC 24 hours. Pressured tested to 1,000 psi. for 30 min. Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By:

CHARLES E. RAMSEY, JR.

TITLE **Area Production Manager**

DATE **September 8, 1965**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: