

OCT 26 1 42 PM '65

THE SUPERIOR OIL CO. - N. MOUNSEY #1
1980' FWL & 660' FSL, SECTION 4-9S-34E
JENKINS (CISCO) FIELD
LEA COUNTY, NEW MEXICO

DRILL STEM TEST DATA

- DST (#1) 9738-9770, CFT on 4-1/2" DP dry, 5/8" BHC, TO 30" w/no blow. Rec 10' DM, no shows. 45" ISIP 3716, FP 139-139, 60" FSIP 3716, HP 5229. BHT 130°.
- DST (#2) 9768-9800 - Pkrs failed.
- DST (#3) 9763-9800 - Pkrs failed.
- DST (#4) 9737-9800 (Bough "C"), CFT on 4-1/2" DP dry, 5/8" BHC. Pkrs set @ 9731 & 9737. TO 5" for pre-flow, strong blow w/GTS 5". Closed in for 30" ISIP. TO 45". Flwd gas to pit on 1/4" surf chk, mud in 23" oil in 28" w/1100 psi TP max. Est rate 20 BOPH of 45.5 gty oil - cut clean w/GOR 1500. SI 1-1/2 hrs. Rev out oil & gas. Rec 90' OCM, no wtr. 30" ISIP 3195, FP 1751-3124, 90" FSIP 3195, HP 5125, BHT 152°.

I certify that the above information is true and complete to the best of my knowledge..



D. H. Collins, Jr.
District Engineer
The Superior Oil Company