

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
E-8835

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name New Mexico 'CQ' State
3. Address of Operator P.O. Box 728 - Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER L , 660 FEET FROM THE West LINE AND 1980 FEET FROM THE South LINE, SECTION 35 TOWNSHIP 10-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat Inbe Permo Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4204' DF	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The following work on subject well has been completed:

1. Spotted 40 sx cement plug over perforations 9707'-9405' in 4-1/2" casing.
2. Loaded casing with mud.
3. Cut off 4-1/2" casing @ 2523'. Pulled 78 joints.
4. Ran 2" tubing and spot 25 sx. cement plug in 4-1/2" casing from 5410'-5070'.
5. Spot 30 sx. cement plug 2573'-2457'.
6. Shoot off 7-5/8" casing @ 1900', 1200' and 800'. Could not recovery any.
7. Spotted 25 sx. cement plug in 7-5/8" casing @ 265'-165'.
8. Spotted 10 sx. cement plug at surface.
9. Installed 4" dry hole marker extending 4' above ground level.
10. Clean location. Plug and Abandon.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Jaschke* TITLE **Assistant District Superintendent** DATE **May 20, 1971**

APPROVED BY *Nathan E. Oleg* TITLE **OIL & GAS INSPECTOR** DATE **DEC 22 1971**

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 21 1971

OIL CONSERVATION COMM.
HOBBS, N. M.