

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
State - E-8835

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	NONE
3. Address of Operator	8. Farm or Lease Name
TEXACO Inc.	State of N. M. "CQ"
4. Location of Well	9. Well No.
UNIT LETTER L 660 FEET FROM THE West LINE AND 1980 FEET FROM	2
THE South LINE, SECTION 35 TOWNSHIP 10-S RANGE 33-E N.M.P.M.	10. Field and Pool, or Wildcat
	South Lane (Penn)
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4204' (D. F.)	Lea

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER Suspend Drilling Operations <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 2180'  
10 3/4" O. D. Casing Cemented at 1966'

After cementing 10 3/4" O. D. Casing at 1966', drilled to 2180' and drilled into water pressure of 1075 pounds.

Cemented from 1590' to 2180' with 300 Sx. regular cement. After a waiting time of 24 Hours set cast iron bridge plug at 1570' and dump 6' of hydromite on top of plug. Spot 30 Sx. Surface plug inside 13 3/8" O. D. Casing. Drilling suspended. Released rig at 2:00 P. M. May 22, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED H. D. Raymond TITLE Assistant District Superintendent DATE MAY 25, 1965

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: