

COUNTY LEA FIELD Inbe STATE NM OWWO
 OPR TEXACO INC. MAP
2 New Mexico "CQ" State
 Sec. 35, T-10-S, R-33-E
 1980' FSL, 660' FWL of Sec. CO-ORD

Re-Cmp 3-13-68			CLASS		EL	
CSG & SX - TUBING			FORMATION	DATUM	FORMATION	DATUM
13 3/8"	215'	250				
10 3/4"	1966'	800				
7 5/8"	3950'	900				
4 1/2"	9799'	1400				
LOGS	EL	GR RA IND HC A				

TD 9800', PBD 9799'

Pennsylvanian Perfs 9704-07' - NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH TYPE WO

3-25-68 F.R.C. 3-28-68; OWWO
 (Orig. Cmp 8-28-65 thru Perf @ 9705', OTD 9800',
 OPB 9764')
 TD 9800', PBD 9799', COMPLETE
 4 1/2" casing collapsed @ 7909'
 Cut 4 1/2" casing @ 4590'
 Set Whipstock @ 4490'
 Drilled to 9800'
 Ran 4 1/2" casing @ 9799' w/400 sx.
 Perf 9704-07' w/2 SPF
 Acid (9704-07') 500 gals.
 Pmpd 51 BO + 3 BW in 24 hrs, Gravity 48.7,
 GOR 380 (9704-07')

COUNTY	LEA	FIELD	Lane, South	STATE	NM
OPR	TEXACO INC.				MAP
2 State of New Mexico "CQ"					
Sec. 35, T-10-S, R-33-E				CO-ORD	
1980' fr S Line & 660' fr W Line of Sec.					
Spd 5-13-65;		CLASS		EL [REDACTED]	
Cmp 8-28-65;		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
13 3/8" at 215' w/250 sx		Yates 2608'			
10 3/4" at 1966' w/800 sx		SA 3885'			
7 5/8" at 3950' w/900 sx		Bo "C" 9700'			
4 1/2" at 9799' w/1400 sx					
LOGS EL GR RA IND HC A					
		TD 9800'; PBD 9764';			
IP(Bough "C") Perf 9705' F 254 BOPD. Pot based on 24 hr test thru 20/64" chk; GOR 1460; Grav 38.2; TP 450#.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Cactus Drlg.	PROP DEPTH	9800'	TYPE
DATE				

F.R. 12-24-64
PD 9800' - Bough "C"
Contractor - Cactus Drlg. Co.
5-17-65 Drlg. 1850'
5-24-65 TD 2180'; Drlg Temporarily Suspended
Heavy flow wtr @ 2180';
6-1-65 TD 2180'; SI
6-7-65 TD 2180'; SI
6-14-65 TD 2180'; SI
6-21-65 TD 2180'; SI
6-28-65 TD 2180'; SI
Final posting until operations resume;
7-26-65 Drlg. 4547' _{lm}
8-2-65 Drlg. 7240'

8-9-65 Drlg. 8562'
8-16-65 Drlg. 9266'
8-23-65 ID 9800'; Running casing
8-30-65 ID 9800'; PBD 9764'; COMPLETE
Perf @ 9705' w/4 shots;
Acid 500 gals;