

COUNTY	LEA	FIELD	Sawyer	STATE	NM
OPR	WESTERN DRILG. CO.			MAP	
1 Great Western-Federal "B"					
Sec. 30, T-9-S, R-38-E				CO-ORD	
1980' fr S Line & 660' fr E Line of Sec.					
Spd 5-24-65		CLASS			
Cmp 6-11-65		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
		Yates 2910			
		SA 4220			
		SA Dolomite			
		4920			
LOGS EL GR RA IND HC A					
TD 5026', PBD 5007'					

IP San Andres Perfs 4925-95' Flwd 2320 MCFGPD + 24 EO + 8 EW.
 Pot. Based on 24 hr test thru 1/2" chk., TP 450#, CP 790,
 gravity (oil) 29.4, GOR 96,667.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton Drilg. Co.	PROP DEPTH	5075'	TYPE
DATE				

	F.R. 4-29-65
	PD 5075' - SA
5-31-65	Drilg. 4678'.
6-7-65	TD 5026', prep to perf.
6-14-65	TD 5026', prep to perf.
6-21-65	TD 5026', PBD 5007', COMPLETED.
	Perf @ 4925', 4927', 4939', 4947', 4957',
	4962', 4965', 4969', 4975', 4976', 4977',
	4985', 4989', 4991', 4994', 4995' W/1 SPI
	Ac. 500 gals (MA)
	Ac. 7000 gals (Reg.)