

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLIC.
(Other instructions on
reverse side)

Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

L. C. 065151

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brown "51"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Sawyer San Andres Oil

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T9S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen a well back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Ralph S. Cooley

3. ADDRESS OF OPERATOR

P. O. Box 254, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface 1650 feet from West Line and 1980 feet from North
line, Section 19, T9S, R38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3959 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Well Progress-Setting 8-5/8" casing
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded - 12:30 P.M. - December 19, 1965

Drilled 12-1/4" hole to 423 feet.

Ran 9 joints 8-5/8" 20# new casing and cemented with 225 sacks regular cement
with 2% CaCl₂. Plug down 2:00 A.M. December 20, 1965. Shoe at 423 feet.
Cement circulated to surface.

W.O.C. - 12 hours.

Tested casing with 600# for thirty minutes. Tested O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Operator

DATE

3/2/66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

APR 1 1966

J. L. GORDON
ACTING DISTRICT ENGINEER

XERO
COPY

XERO
COPY

XERO
COPY

XERO
COPY