

COUNTY	LEA	FIELD	Mescalero	STATE	NM
OPR	DALBY, ARNO R.				MAP
	1 State				
	Sec. 10, T-10-S, R-32-E				CO-ORD
	1650' FSL, 330' FEL of Sec.				MN 21704
	Spd 12-11-65		CLASS	EL	
	Cmp 2-12-66		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
8 5/8" 391' 250					
4 1/2" 4187' 225					
LOGS EL GR RA IND HC A					
			TD 4187'		

IP San Andres Perfs 4124-50' Pmpd 42 BOPD + 158 BW. Pot.
Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Verna Drlg. Co.	PROP DEPTH	4300'	TYPE
DATE				

	F.R. 11-24-65
	PD 4300' - SA
	Contractor - Verna Drlg. Co.
12-13-65	TD 391', prep to drill.
12-20-65	Drlg. 3916'.
1-3-66	TD 4187', tstg on pump.
	Cored 4121-79', rec 55' Being:
	2' dns lm;
	51' lm., frac, bldg oil;
	2' dns lm.
	Perf @ 4124', 4138', 4142', 4150' W/1 SPI
	Ac (4124-50') 2000 gals.
	Pmpd 124 BF in 24 hrs (20% oil).
1-10-66	TD 4187', tstg on pump.
	Pmpd 100 BF in 24 hrs (7% oil).

LEA Mescalero
DALBY, ARNO R., #1 State

NM

Sec. 10-10S-32E
Page #2

1-17-66 TD 4187', tstg on pump.
1-24-66 TD 4187', tstg on pump.
1-31-66 TD 4187', tstg on pump.
Pmpd approx. 100 BF per day (7-10% oil)
2-7-66 TD 4187', tstg on pump.
2-14-66 TD 4187', tstg on pump.
2-21-66 TD 4187', tstg on pump.
2-28-66 TD 4187', tstg on pump.
3-7-66 TD 4187', tstg on pump.
3-14-66 TD 4187', tstg on pump.
3-21-66 TD 4187', COMPLETE.
LOG TOPS: Anhydrite 1560', Yates 2220',
San Andres 3430'.