

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.C.
NEW MEXICO OIL CONSERVATION COMMISSION

APR 5 11 20 AM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator H. K. Byron	8. Farm or Lease Name State 5
3. Address of Operator Box 147 - Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER I , 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 10S RANGE 36E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4017.1 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-30-66: Spudded in.

4-3-66: Drilled to 288 and cemented 285' of 28# 8-5/8" used casing, with 100 sacks of regular cement with 4% gel and 2% calcium chloride. Cement circulated to surface. The surface was set with cable tools in a 10-3/4" hole. We hit the water sand at 140-150'. Work completed at 2:30AM on 4-3-66.

4-4-66: Bailed hole dry. Let set for 30 minutes and casing did not leak. Drill ahead with cable tools until Verna Drilling Co. rotary rig can move to location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *H. K. Byron* TITLE **Geologist** DATE **4-4-66**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: