

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.C.
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 6 2 52 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator G. W. Strake		8. Farm or Lease Name D. H. Crockett, et al
3. Address of Operator 511 Midland Tower, Midland, Texas		9. Well No. 1
4. Location of Well UNIT LETTER L , 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 9S RANGE 35E NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4174 G.L.		12. County Lee

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-29-66 Spudded 15" surface hole and drilled to total depth of 375' KDB in anhydrite. Cemented 385.00' of 12 3/4" OD 33.38# H-40 casing at 375' KDB with 300 sacks of regular cement with 2% calcium chloride added. Cement circulated. Plug down at 9:00 P.M., 4-29-66. W.O.C.**
- 4-30-66 Pressure tested 12 3/4" surface casing at 3:30 P.M. with 600 psi for 30 minutes with no loss in pressure. Drilled plug at 4:00 P.M., 4-30-66.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *CRP* TITLE Gen. Supt. DATE May 5, 1966

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: