

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSIONS OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

JUN 9 11 41 AM '66

5. Kind of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
6. State Oil & Gas Lease No.	<b>NM 315</b>
7. Unit Agreement Name	
8. Farm or Lease Name	<b>J.P. Collier</b>
9. Well No.	<b>3</b>
10. Field and Pool, or Wildcat	<b>North Bagley</b>
12. County	<b>Lea</b>

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator <b>TEXAS PACIFIC OIL COMPANY</b>
3. Address of Operator <b>P.O. Box 1069 - Hobbs, New Mexico</b>
4. Location of Well UNIT LETTER <b>C</b> <b>810</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>West</b> LINE, SECTION <b>10</b> TOWNSHIP <b>11-S</b> RANGE <b>33-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>4266.7' GL</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Layed down drill pipe. Ran 116 jts. 32# H-40 8-5/8" csg. Set @ 3776'.
- Cemented w/235 sks. 50-50 Poz Mix plug 6% gel and 150 sks. incor plus 1% Ca Cl.
- Pumped plug to 3710'. W.O.C. 18 hrs.
- Tested 8-5/8" csg. to 1200#. Test OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Richard D. Bland* TITLE **Area Superintendent**

DATE **6-8-66**

APPROVED BY *John A. Harvey*  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE