

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruction re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 015908

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ APR 25 AM '67	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR J. C. WILLIAMSON	8. FARM OR LEASE NAME MURPHY-FEDERAL
3. ADDRESS OF OPERATOR BOX 16, MIDLAND, TEXAS 79701	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 660' FNL of Section 4	10. FIELD AND POOL, OR WILDCAT WILDCAT
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 4-9S-35E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4207' DF	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9770' Line
13 3/8" - 357' - 350
8 5/8 4029 - 250
4 1/2 9745 - 350
2" FUE - 9755

Plugged and Abandoned November 16, 1966

Recovered 4649' of 4 1/2" casing

Recovered 1004' of 8 5/8" casing

Set 50 sx cement in bottom 9770 - 9570', Set 25 sx cement @ stub of 4 1/2" casing 4649',
Set 25 sx cement @ 4029', set 50 sx cement @ stub of 8 5/8" casing 1004', 25 sx cement
@ bottom of surface casing 357' and 10 sx cement in top surface. Welded plate on and
set marker according to the Rules and Regulations.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Prod. Engineer

DATE

Nov. 29, 1966

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APR 8 1967
J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.