

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Lario Oil & Gas Company	8. FARM OR LEASE NAME Amerada Federal
3. ADDRESS OF OPERATOR Box 1209 Odessa, Texas	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1990 feet from West line and 1980 feet from North line	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA N 1/4 Sec. 26, 9-S Twp. 32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4344 ground level	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

August 10, 1966: Total depth drilled 4470' Lime.

Fill casing with mud.

Spot 90 sack cement plug from 4470 to 4170

Spot 30 sack cement plug from 2280-2180; Spot 50 sack cement plug from 1750 to 1600; spot a 6 sack cement plug zero to 20 feet. Put piece of 4" pipe in surface cement extending 4" above ground. Fill cellar and clean location.

Humble Oil & Refining Company, Mr. L. E. Sewell, Humble Building, Midland, Texas
Union Texas Petroleum, Mr. Pat Baines, 1300 Wilco Building, Midland, Texas
Adam E. Crafe Assoc., Inc., Mr. J. Minahan, 220 Wilkinson-Foster Building, Midland, Texas
Amerada Oil Corporation, Mr. John Cornwall, Box 591, Midland, Texas

18. I hereby certify that the foregoing is true and correct

SIGNED J. L. GordonTITLE Dist. Prod. Supt.DATE 8-15-66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED _____

DATE _____

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.