DISTRIBUTION			Form C-103
			Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVAT	TON COMMISSION	C-102 and C-103
FILE	KEW MEXICO OF CONCERTA	TON COMMISSION	Effective 1-1-65
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE	941 1	±4 00 14 00	State Fee
OPERATOR			5. State Oil & Gas Lease No.
			00G- 260
STINDS	V NOTICES AND DEPORTS ON WELL	·	mmilitariin
(DO NOT USE THIS FORM FOR PR	RY NOTICES AND REPORTS ON WELL PROSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 10N FOR PERMIT -" (FORM C-101) FOR SUCH PROPO	O DIFFERENT RESERVOIR.	
1.	TON TON PERMIT = (FORM C-TOT) FOR SUCH PROPE	SALS.)	7. Unit Agreement Name
OIL GAS WELL	OTHER.		
2. Name of Operator			8. Farm or Lease Name
3. Address of Operator	onal Petroleum Corporation		9. Well No.
			5. Well 110.
201 Well Blds. S	tite 308, Midland, Texas		1
1			10. Field and Pool, or Wildcat
UNIT LETTER	180 FEET FROM THE South LINE	AND 1980 FEET FROM	Engoy
· ·			
THE LINE, SECT	on <u>10</u> township <u>11 S</u> F	ANGE 33 B NMPM.	
	15. Elevation (Show whether DF, RT ,	GR, etc.)	12. County
<u> </u>	4254.8 GB		Lea
16. Check	Appropriate Box To Indicate Nature	of Notice Report of Ot	ner Data
	ITENTION TO:		REPORT OF:
		302324021	REPORT OF.
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMED	IAL WORK	
TEMPORARILY ABANDON	<u>-</u>	=	ALTERING CASING
PULL OR ALTER CASING		NCE DRILLING OPNS.	PLUG AND ABANDONMENT
		TEST AND CEMENT JOB	
OTHER	OTH.	ER	
17. Describe Proposed or Completed Or	erations (Clearly state all pertinent details, and	give pertinent dates, including	
Decertor i repeded of completed of			estimated date of starting any proposed
work) SEE RULE 1 103.	. ,		estimated date of starting any proposed
worky see Note 1103.			
worky see Note 1103.			
Drilled 11" hole TD	37551. Ren Floatshoe and Float	scollar, 2.72. Ran	controlizer consensities
Drilled 11" hole TD	37551. Rem Floatshoe and Float 2nd. collar. Ran 288.861, J5	scollar, 2.72: Ran 5 32# 8 5/8". Ran 1	######################################
Drilled 11" hole TD	37551. Rem Floatshoe and Float 2nd. collar. Ran 288.861, J5	scollar, 2.72: Ran 5 32# 8 5/8". Ran 1	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24#	37551. Rem Floatshoe and Float 2nd. collar. Ran 288.861, J59 8 5/8" Casing Set @ 37551 Rot	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	37551. Rem Floatshoe and Float 2nd. collar. Ran 288.861, J59 8 5/8" Casing Set @ 37551 Rot	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20 J55 24#	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72 . Ran 5 32# 8 5/8". Ran 1 sary KB. Test pipe	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento W00 24 hrs. Drilling	2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rosed with 200 sacks Encor and 18 ahead 7 7/8" hole, 10-5-66.	scollar, 2.72: Ran 5 32# 8 5/8# Ran 1 Sary KB. Test pipe 30 sacks Incor with	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento WOO 24 hrs. Drilling	3755'. Ran Floatshoe and Float 2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks Encor and 18	scollar, 2.72: Ran 5 32# 8 5/8# Ran 1 Sary KB. Test pipe 30 sacks Incor with	Gentralizer ####################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento WOO 24 hrs. Drilling	2nd. collar. Ran 288.86', J5: 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks incor and 18 ahead 7 7/8" hole, 10-5-66.	secollar, 2.72*. Ran 1 Sary KB. Test pipe 20 sacks Incor with	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento WOO 24 hrs. Drilling	2nd. collar. Ran 288.86', J59 8 5/8" Casing Set @ 3755' Rosed with 200 sacks Encor and 18 ahead 7 7/8" hole, 10-5-66.	secollar, 2.72*. Ran 1 Sary KB. Test pipe 20 sacks Incor with	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento W00 24 hrs. Drilling	2nd. collar. Ran 288.86', J5: 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks incor and 18 ahead 7 7/8" hole, 10-5-66.	secollar, 2.72*. Ran 1 Sary KB. Test pipe 20 sacks Incor with	######################################
Drilled 11" hole TD mid first Jt. and on Ran 1956.20: J55 24# 1000 PSI OK. Comento WOO 24 hrs. Drilling	2nd. collar. Ran 288.86', J5: 8 5/8" Casing Set @ 3755' Rot ed with 200 sasks incor and 18 ahead 7 7/8" hole, 10-5-66.	secollar, 2.72*. Ran 1 Sary KB. Test pipe 20 sacks Incor with	######################################

CONDITIONS OF APPROVAL, IF ANY: