

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JAN 24 11 53 AM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG-5210-2 Tract 1
7. Unit Agreement Name -
8. Farm or Lease Name Tenneco-State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER- **Dry**

2. Name of Operator
T. F. Hodge

3. Address of Operator
1605 Continental Bank Bldg., Fort Worth, Texas

4. Location of Well
UNIT LETTER **N**, **1846** FEET FROM THE **West** LINE AND **660** FEET FROM
THE **South** LINE, SECTION **31** TOWNSHIP **11-S** RANGE **34-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4222 D.F.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

It is the intention of T. F. Hodge to P&A this well in the following manner after conferring with Mr. Joe Ramey, Hobbs, New Mexico, on December 10, 1966:

Hole loaded with 9.3#/gal. mud; spot the following cement plugs through D.P.:
25 sx @ T.D. of 10,340'; 25 sx @ top of WC lime @ 9120'; 25 sx @ 7720'; 25 sx @ 5490'; 25 sx in bottom of 8 5/8" csg. @ 3981'; 25 sx @ cut off of 8 5/8" csg. @ 1700'; 25 sx in bottom of surface csg. @ 380'; and 10 sx plug in top of surface csg. with appropriate 4-1/2" OD marker in top of surface casing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Marshall B. Gook* TITLE **Petroleum Engineer** DATE **1-18-67**

APPROVED BY *Joe Ramey* TITLE **Inspector** DATE

CONDITIONS OF APPROVAL, IF ANY: